

DM-190GS

IP65, Robust Industrial Monitors



- ◆ [Feature](#)
- ◆ [Ordering Information](#)
- ◆ [See Large Image\(s\)](#)

Download

- + [Downloads](#)
- + [Catalog](#) 

Features

1. Aluminum front panel meets IP65 standard for tough working environment
2. Optional RS-232 interface touch screen
3. Robust chassis and retention kit structure for shocking and vibration requirement
4. Over 300cd/m² high brightness and 50000hrs MTFB long lifetime panel
5. Analog VGA interface supports most of general system boards
6. M models support 9~36V DC power input for mobile application

Specifications

LCD Size	19"
Input Interface	Analog VGA + DVI-D
Max Resolution	Analog VGA + DVI-D
Brightness (cd/m²)	300
Contrast Ratio	800:1
Display Color	16.2M
Pixel Pitch (mm)	0.294
Front Frame	Aluminum
Chassis	Heavy-duty steel
View Angle (H/V)	160/160
Input Voltage	12VDC or 9-36VDC
OSD function	Yes
Smart OSD	Yes
Mounting	Wall/Panel/Rack/Arm (100x100)/Stand
Color	Silver
Dimension(W x H x D mm)	482 x 399 x 73
Operating Temperature	0~50 °C
Front Panel Protection	IP65
Net Weight	10 kgs
Power Adapter	45W, 63000-UP0451E12P81L-RS

Ordering Information

Part No.	Description
DM-190GS-R11/T-R	19" 300cd/m ² SXGA LCD Monitor, Aluminum Front Panel, Silver Color,W / Touch Screen,RoHS
DM-190GMS-R11/T-R	19" 300cd/m ² SXGA LCD Monitor, Aluminum Front Panel, Silver Color,W / Touch Screen,9~36V DC input,RoHS
DM-190GS-USB-R11/T-R	19" 300cd/m ² SXGA LCD Monitor,Aluminum Front Panel,Silver Color,W/19" USB Touch Screen,RoHS 7
DM-190GMS-USB-R11/T-R	19" 300cd/m ² SXGA LCD Monitor,Aluminum Front Panel,Silver Color,W/19" USB Touch Screen,9~36V DC input,RoHS

Packing List

1 * AC Power Cable	1 * VGA Cable
1 * VGA Cable	1 * User Manual
1 * Power Cable for Terminal Block (For M model ONLY)	1 * Touch Screen RS-232 Cable / Touch Pen / Driver CDROM (For T-R model)
1 * Touch Screen USB Cable / Touch Pen / Driver CDROM (For USB/T-R model)	